### TCS-1

#### Tent-X Control System

The Tent-X (TCS-1) control system is a state-of-the-art control system, designed for single-zone grow tents. The Tent-X offers users control of both the environment and the irrigation, in one single controller. It is the brain that unites all your climate control and irrigation devices into one being, allowing your devices to work together in order to create the optimal growth environment for your plants.



It comes with a 3-in-1 temperature, humidity, and light sensor, the MBS-TH. Users can daisy-chain the MBS-TH sensor with the CO2 sensor (MBS-S8), the full spectrum quantum sensor (MBS-PAR), and the smoke and water detectors into Tent-X's SENSOR port.

You can also connect an AMP-3 sensor board to the Tent-X and the WCS-1/2/3 sensors or the WD-1 water detector to the sensor board. Additionally, Tent-X supports the connection of up to four DS plug-in control modules. You can assign your pumps and valves to the Tent-X using the Program modules, and set up irrigation schedules. You can set single schedules, multiple schedules, and recycle timer.

\*Due to the compact environment of a grow tent, you can only assign a single sensor for each type of sensor.

The Tent-X is intended to be used by growers who want a compact control system for their grow tents. It is also modularly designed, allowing for system customization based on a grower's needs.

# **Specifications**

TCC-1

### **Input Voltage**

Voltage	100-240VAC, 50/60Hz

# **Working Environments**

Temperature	32°-122°F (0-50°C)	
Humidity	≤90%	

## **Product Dimensions**

Size	6.52inch / 165.58mm(L) x 3.78inch / 96mm(W) x 1.63inch / 41.5mm(H)
Net Weight	0.54lbs / 0.243kg

#### **Package Dimensions**

Size	10.83inch / 275mm(L) x 6.46inch / 164mm(W) x 2.55inch / 65mm(H)
Gross Weight	1.98lbs / 0.90kg

#### Display & Control

Save/Copy/ Import/ Export data	Micro SD	
Language:	English (International)	
Control	Button Control	
	128x128 LCD Display	

#### **Package Contents**

Tent-X Controller	
Temp / Humid / Light 3-in-1 Sensor	1pc
16ft RJ12 Cable	1pc
12V Power Adapter	1pc
RJ12 Y-Splitter	1pc
4ft M12 Cable	1pc
4ft RJ12 Cable	1pc

#### **Product Capacity**

MBS-TH (Temp / Humid / Light)	Max 1pc
MBS-S8 (CO2)	Max 1pc
MBS-PAR (PPFD)	Max 1pc
MBS-SD (Smoke Detector)	Мах 1рс
AMP-3 (pH / EC / Temp)	Мах 1рс
WCS-1/2/3 (WC / EC / Temp)	Мах 1рс
WD-1 (Water Detector)	Max 2pcs
Temperature Device Stations	Max 2pcs
Humidity Device Stations	Max 2pcs
CO2 Device Stations	Max 2pcs
Timer Device Stations	Max 4pcs
EC Fan Control Adaptor	Max 2pcs
Light Channels	Max 2lines

# **Link Up**

TCS-

### **CONNECTION DIAGRAM**

